

Name	SC-SPIRIT LLX "LOW LOSS"
Properties	Analog
Properties	OFC oxygen free copper
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application area	Installation
Application area	Studio / Broadcast
Application	Instrument Cable
Colour	black
Colour detailed	black
Signal transmission	asymmetrical
Construction	LI2Y(LS)CY 1x0,38mm ²
Jacket material	PVC
Jacket Ø [mm]	7,50
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm²]	0,38
Inner conductor Ø (audio) [mm]	0,70
AWG (audio)	21
Shielding	Copper braided shielding + semiconductor
Copper strands (audio)	19
Copper strand Ø (audio) [mm]	0,16
Conductor insulation material	Foam / Skin-PVC
Weight per 1 m [g]	62,2
UV-resistant	yes
Fire load per m [kWh]	0,26
Style variant	round
Shielding factor [%]	100
Packing	100 m
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	7,5
Height [mm]	7,5
Capac. cond./shield. per 1 m (audio) [pF]	52
Capacity wire/electic screen at 1 ft. (audio) [pF]	15,8496
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	48
Conductor resistance per 1000 ft. [Ω]	14,6304
EAN	4049371220248