

|  |  |
|--|--|
| <b>Name</b>  | Tricone® XXL                             |
| <b>Properties</b>  | OFC oxygen free copper                   |
| <b>Properties</b>  | Analog                                   |
| <b>Application area</b>                                    | Studio / Broadcast                       |
| <b>Application area</b>                                    | Mobile outdoor / indoor                  |
| <b>Application area</b>                                    | Stage / live                             |
| <b>Application area</b>                                    | Installation                             |
| <b>Application</b>   | Instrument Cable                         |
| <b>Colour</b>  | black                                    |
| <b>Colour detailed</b>                                     | black                                    |
| <b>Signal transmission</b>                                 | asymmetrical                             |
| <b>Construction</b>  | LI2Y(LS)CY1x0,50mm2                      |
| <b>Jacket material</b>                                     | LLC (Long Life Compound)                 |
| <b>Jacket Ø [mm]</b>                                       | 5,90                                     |
| <b>Number of Channels (audio)</b>                          | 1  |
| <b>Inner conductor (audio)</b>                             | 1  |
| <b>Inner conductor (audio) [mm²]</b>                       | 0,50                                     |
| <b>Inner conductor Ø (audio) [mm]</b>                      | 0,80                                     |
| <b>AWG (audio)</b>   | 20                                       |
| <b>Shielding</b>   | Copper spiral tin-plated + semiconductor |
| <b>Copper strands (audio)</b>                              | 28                                       |
| <b>Copper strand Ø (audio) [mm]</b>                        | 0,15                                     |
| <b>Conductor insulation material</b>                       | Foam / Skin-PE                           |
| <b>Conductor insulation Ø [mm]</b>                         | 2,80                                     |
| <b>Weight per 1 m [g]</b>                                  | 44                                       |
| <b>UV-resistant</b>  | yes                                      |
| <b>Fire load per m [kWh]</b>                               | 0,27                                     |
| <b>Style variant</b>                                       | round                                    |
| <b>Shielding factor [%]</b>                                | 100                                      |
| <b>Packing</b>   | 500 m spool                              |
| <b>Packing</b>   | 100 m spool                              |
| <b>Temperature min. [°C]</b>                               | -25                                      |
| <b>Temperature max. [°C]</b>                               | 60                                       |
| <b>Width [mm]</b>  | 5,9                                      |
| <b>Height [mm]</b>   | 5,9                                      |
| <b>Capac. cond./shield. per 1 m (audio) [pF]</b>           | 85                                       |
| <b>Capacity wire/electric screen at 1 ft. (audio) [pF]</b> | 25,908                                   |
| <b>Insulation resist. per 1 km [GΩ]</b>                    | 1  |
| <b>Insulation resist. per 1000 feet [GΩ]</b>               | 0,3048                                   |
| <b>Insulation resist. per 1 km (audio) [GΩ]</b>            | 1  |
| <b>Insulation resist. per 1000 feet (audio) [GΩ]</b>       | 0,3048                                   |
| <b>Conductor resistance per 1 km [Ω]</b>                   | 90                                       |
| <b>Conductor resistance per 1000 ft. [Ω]</b>               | 27,432                                   |
| <b>EAN</b>   | 4049371050920                            |