

|  |                            |
|--|----------------------------|
| <b>Name</b>  | SC-Orbit 240 MKII, HighEnd |
| <b>Properties</b>                                    | OFC oxygen free copper     |
| <b>Properties</b>                                    | Analog                     |
| <b>Application area</b>                              | Studio / Broadcast         |
| <b>Application area</b>                              | Installation               |
| <b>Application</b>                                   | Speaker Cable              |
| <b>Colour</b>  | black                      |
| <b>Colour detailed</b>                               | black transparent          |
| <b>Construction</b>                                  | 2LIY4,00mm <sup>2</sup>    |
| <b>Jacket material</b>                               | PVC                        |
| <b>Jacket Ø [mm]</b>                                 | 0,00                       |
| <b>Number of Channels (audio)</b>                    | 1                          |
| <b>Inner conductor (audio)</b>                       | 2                          |
| <b>Inner conductor (audio) [mm<sup>2</sup>]</b>      | 4,00                       |
| <b>Inner conductor Ø (audio) [mm]</b>                | 2,26                       |
| <b>AWG (audio)</b>                                   | 11                         |
| <b>Copper strands (audio)</b>                        | 1036                       |
| <b>Copper strand Ø (audio) [mm]</b>                  | 0,07                       |
| <b>Weight per 1 m [g]</b>                            | 121                        |
| <b>UV-resistant</b>                                  | yes                        |
| <b>Fire load per m [kWh]</b>                         | 0,21                       |
| <b>Style variant</b>                                 | twin                       |
| <b>Packing</b>                                       | 100 m spool                |
| <b>Temperature min. [°C]</b>                         | -30                        |
| <b>Temperature max. [°C]</b>                         | 70                         |
| <b>Width [mm]</b>                                    | 12                         |
| <b>Height [mm]</b>                                   | 5,9                        |
| <b>Capac. cond./cond. per 1 m (audio) [pF]</b>       | 55                         |
| <b>Capacity wire/wire at 1 ft. (audio) [pF]</b>      | 16,764                     |
| <b>Insulation resist. per 1 km [GΩ]</b>              | 0,01                       |
| <b>Insulation resist. per 1000 feet [GΩ]</b>         | 0,003                      |
| <b>Insulation resist. per 1 km (audio) [GΩ]</b>      | 0,01                       |
| <b>Insulation resist. per 1000 feet (audio) [GΩ]</b> | 0,003                      |
| <b>Conductor resistance per 1 km [Ω]</b>             | 4,5                        |
| <b>Conductor resistance per 1000 ft. [Ω]</b>         | 1,3716                     |
| <b>EAN</b>   | 4049371003025              |