

Name	SC-CORONA
Properties	Analog
Properties	OFC oxygen free copper
Application area	Studio / Broadcast
Application	NF-Phono cable
Colour	transparent
Colour detailed	transparent
Signal transmission	asymmetrical
Construction	(LIHS09YHS1x0,50mm <sup>2</sup> )CY
Jacket material	PVC
Jacket Ø [mm]	6,70
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm <sup>2</sup> ]	0,50
AWG (audio)	20
Shielding	Copper braided shielding + semiconductor
Copper strands (audio)	28
Copper strand Ø (audio) [mm]	0,15
Conductor insulation material	PE
Weight per 1 m [g]	51
Fire load per m [kWh]	0,25
Style variant	round
Shielding factor [%]	100
Packing	bulk stock
Packing	50m spool
Temperature min. [°C]	-40
Temperature max. [°C]	80
Width [mm]	6,7
Height [mm]	6,7
Capac. cond./shield. per 1 m (audio) [pF]	78
Capacity wire/electic screen at 1 ft. (audio) [pF]	23,7744
Insulation resist. per 1 km [G&#8486;]	0,01
Insulation resist. per 1000 feet [G&#8486;]	0,003
Insulation resist. per 1 km (audio) [G&#8486;]	0,01
Insulation resist. per 1000 feet (audio) [G&#8486;]	0,003
Conductor resistance per 1 km [G&#8486;]	36
Conductor resistance per 1000 ft. [G&#8486;]	10,9728
EAN	4049371003216