

<b>Name</b>	SC-CLUB RED ZILK
<b>Properties</b>	Analog
<b>Properties</b>	Digital 110 Ω AES / EBU
<b>Properties</b>	OFC oxygen free copper
<b>Application area</b>	Mobile outdoor / indoor
<b>Application area</b>	Installation
<b>Application area</b>	Studio / Broadcast
<b>Application</b>	Microphone Cable
<b>Colour</b>	red
<b>Colour detailed</b>	wine-red
<b>Signal transmission</b>	symmetrical
<b>Construction</b>	(2LI2Y0,25mm <sup>2</sup> )(ST)CY
<b>Jacket material</b>	S-PVC
<b>Jacket Ø [mm]</b>	7,30
<b>Number of Channels (audio)</b>	1
<b>Inner conductor (audio)</b>	2
<b>Inner conductor (audio) [mm<sup>2</sup>]</b>	0,25
<b>AWG (audio)</b>	23
<b>Shielding</b>	Copper spiral shielding 95 % + carbon semiconductor
<b>Copper strands (audio)</b>	65
<b>Copper strand Ø (audio) [mm]</b>	0,07
<b>Conductor insulation material</b>	HD-PP Gas-injected
<b>Conductor insulation Ø [mm]</b>	1,55
<b>Weight per 1 m [g]</b>	53,4
<b>Fire load per m [kWh]</b>	0,2
<b>Style variant</b>	round
<b>Shielding factor [%]</b>	100
<b>Packing</b>	bulk stock
<b>Packing</b>	100 m spool
<b>Temperature min. [°C]</b>	-25
<b>Temperature max. [°C]</b>	70
<b>Width [mm]</b>	7,3
<b>Height [mm]</b>	7,3
<b>Capac. cond./cond. per 1 m (audio) [pF]</b>	50
<b>Capacity wire/wire at 1 ft. (audio) [pF]</b>	15,24
<b>Capac. cond./shield. per 1 m (audio) [pF]</b>	100
<b>Capacity wire/electic screen at 1 ft. (audio) [pF]</b>	30,48
<b>Impedance [Ω]</b>	110
<b>Insulation resist. per 1 km [GΩ]</b>	0,2
<b>Insulation resist. per 1000 feet [GΩ]</b>	0,061
<b>Conductor resistance per 1 km [Ω]</b>	78
<b>Conductor resistance per 1000 ft. [Ω]</b>	23,7744
<b>Shield. resistance per 1 km [Ω]</b>	10
<b>Shield. resistance per 1000 ft. [Ω]</b>	3,048
<b>EAN</b>	4049371237161