

Name	Meridian Mobile SP240
Properties	Analog
Properties	OFC oxygen free copper
Application area	Stage / live
Application area	ELA 100 V
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application	Speaker Cable
Colour	black
Colour detailed	black
Construction	(2LIY4,0mm ²)Y
Jacket material	PVC
Jacket Ø [mm]	9,50
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	4,00
Inner conductor Ø (audio) [mm]	2,76
AWG (audio)	11
Copper strands (audio)	56
Copper strand Ø (audio) [mm]	0,30
Conductor insulation Ø [mm]	4,20
Weight per 1 m [g]	150
UV-resistant	yes
Fire load per m [kWh]	0,46
Style variant	round
Packing	100 m spool
Packing	500 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	9,5
Height [mm]	9,5
Capac. cond./cond. per 1 m (audio) [pF]	125
Capacity wire/wire at 1 ft. (audio) [pF]	38,1
Insulation resist. per 1 km [GΩ]	0,005
Insulation resist. per 1000 feet [GΩ]	0,0015
Insulation resist. per 1 km (audio) [GΩ]	0,005
Insulation resist. per 1000 feet (audio) [GΩ]	0,0015
Conductor resistance per 1 km [Ω]	4,5
Conductor resistance per 1000 ft. [Ω]	1,3716
EAN	4049371206419